

250 Staunton Turnpike, Parkersburg, WV 26104


## 8800 Series **Vinyl Awning Window** "IMPACT"

## **EVALUATED FOR USE IN THE STATE OF TEXAS**


The Wincore Awning Window described herein complies with the 2006 International Residential Code (IRC), Sections R308.6 and the 2006 International Building Code (IBC), Sections 1405.12, 1609, 1714.5, 2403 and 2404 (including Texas revisions) subject to the following conditions:

- 1. Anchors shall be as listed and spaced as shown in the details. Anchor embedment to base material shall be beyond roof covering.
- 2. When used in areas requiring wind-borne debris protection (Seaward and Inland I areas), this product complies with Section R301.2.1.2 of the IRC and Section 1609.1.2 of the IBC and does not require impact protection. This product meets missile level "D" and includes Wind Zone 4 as defined in ASTM E 1996.
- 3. Allowable design pressure requirements must be equal to or less than the design pressure rating shown in the design pressure chart, sheet 1 of this drawing.
- Conditions not covered by this drawing are subject to further engineering analysis.

	TABLE OF CONTENTS
SHEET#	DESCRIPTION
1	Typical elevations, design pressures and general notes
2	Vertical & horizontal cross sections & frame anchoring
3	Bill of materials, components and glazing detail




MAX. FRAME DIMENSION	MAX. D.L.O. DIMENSION	GLASS TYPE	DESIGN PRE	SSURE (PSF)
53.0" X 32.0"	46.54" X 25.54"	<b>G</b> 1	+50.0	-50.0



SCALE: N.T.S. DWG. BY: LFS


TX-4241




- Projects\Project Folders\Proj 1601 - 1700\PF 1677\D. RWBC Drawings\Casement Window\TX-4240.dwg. 2.2


	BILL OF MATERIALS				
ITEM #	DESCRIPTION	MATERIAL			
В	2X BUCK SG >= 0.42	WOOD			
С	1/4" MAX. SHIM SPACE	-			
F	#8 X 2-1/2" PPH WOOD SCREW	STEEL			
G	#8 X 2-1/2" PFH WOOD SCREW	STEEL			
Н	#8 X 1" PFH WOOD SCREW	STEEL			
1	FRAME*	PVC			
2	SASH *	PVC			
3	GLAZING BEAD*	PVC			
7	WEATHERSTRIP AMESBURY (CS 120 33-SEAL)	FOAM			
8	WEATHERSTRIP AMESBURY (12300 SEAL)	VINYL			
9	WEATHERSTRIP ULTRA FAB .250 (PILE - 250 - KP52)	VINYL			
10	MULTI-POINT LOCK (TRUTH) 24.33.32.004	-:			
12	OPERATOR (TRUTH) 50.10.00.011	-0			
24	SNUBBER (TRUTH) (SASH) 21642	<b>-</b> ,			
25	SNUBBER (TRUTH) (FRAME) 32938	=			


<sup>\*</sup> THE APPROVED WHITE RIGID PVC EXTERIOR EXTRUSIONS FOR WINDOWS ARE TO BE PRODUCED BY EXTRUDERS LICENSEES IN "AAMA CERTIFICATION PROGRAMS FOR RIGID PVC EXTRUSIONS".











GLAZING BEAD

PRODUCT:   8800 SERIES	Documents Prepared By: Lyndon F.	Day BUILDING CONSULTANTS, I	P.O. Box 230 Valrico FL.			
REVISIONS		Vinyl Awning Window	PART OR ASSEMBLY:	STATISCULO STATEMENT TO THE	BILL OF MAIERIALS, COMPONENTS	AIND GLAZING DEIAIL
1						REVISIONS